

CLASSIFICATION: TOP SECRET
GROUP 1, EXCLUDED FROM AUTOMATIC DOWNGRADING AND DECLASSIFICATION

SR/0135/55/000/004/2022/0013

21.791.763.11-68.3-45.11.1.1

AUTHOR: Rubanovich, B. B. (Engineer); Isekovich, A. A. (Engineer); Sinyakov, N. I., V. A. (Engineer)

Control panels

Doc. No. 1961. 22-2

Panel, aluminum, lad size, 1.5 x 1.5 m, with its own electrical connections

1. The panel is made of aluminum. It is equipped with 10 EPTs (adhesive tape) of size 10 x 10 cm, 10 polyester MCF-9 or MCF-10, 10 polyester MCF-9 or MCF-10, and 10 parts cement as follows: 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement, 10 parts cement.

panels were 50% higher than without the adhesive. Orig. art. has 4 figures and 2 tables.

Cord 1/2

ASSOCIATION: TsNIISK Gosstroya SSSR

SUBMITTED: 00

ENCL: 00

SUB CODE: IE, MT

OTHER: 000

RUBANOVICH, B.B., inzh.; ITSKOVICH, A.A., inzh.; SINYAKOVSKIY, V.A., inzh.

Spot welding over glue of structural elements. Svar. proizv.
no.4:22-25 Ap '65. (MIRA 18:6)

1. TSentral'nyy nauchno-issledovatel'skiy institut stroitel'-
nykh konstruktsiy Gosstroya SSSR.

L 2299-66 ENP(a)/EWT(m)/EPF(c)/ENP(i)/ENP(v)/ENP(j)/T/ENP(t)/ENP(k)/ENP(b)/

EWA(c) JD/WW/HM/RM/WH
ACCESSION NR: AP5020166

UR/0135/65/000/008/0033/0034
621.791.039

AUTHORS: ^{44.65}Itskovich, A. A. (Engineer); ^{48B}Sinyakovskiy, V. A. (Engineer); ^{44.55}Rubanovich, B. B. (Engineer)

^{44.65}TITLE: Apparatus for preparation of aluminum alloy surfaces for ^{15, 44.55}adhesive-welded connections

SOURCE: Svarochnoye proizvodstvo, no. 8, 1965, 33-34

TOPIC TAGS: metal bonding, ¹⁸welding, adhesive bonding, surface finish, surface preparation

ABSTRACT: Since bonded joint quality depends to a large extent on the preparation of the bonded surfaces, an optimum chemical or mechanical surface preparation method should be used for each bonding method. For mechanical surface preparation small steel wire brushes (wire diameter 0.2 mm, outside diameter 100 mm, inside diameter 30-40 mm, width 8-15 mm, speed 1200-3000 rpm) are recommended for best results. The authors developed a simple apparatus for cleaning large construction parts (up to 6 m long) at a speed of up to 2.5 m/min. It consists of a 1 kw, 930 rpm motor with a 250-mm long horizontal pendulum lever pivoted on the motor axis.

Card 1/2

L 2299-66

ACCESSION NR: AP5020166

The end removed from the motor has a bearing-mounted axle driven by V-belts from the motor (2:1 speed increase) on which 2-5 brushes can be mounted. The brushes are held against the work by a damping system consisting of two opposing springs which provide almost constant contact force despite slight irregularities of the work piece. The surface produced is evaluated at 2-60 μ ohms for welding. The aluminum dust should be removed from the surface by brushing or with alcohol (acetone is not acceptable). Orig. art. has: 2 figures.

ASSOCIATION: none

SUBMITTED: 00

ENCL: 00

SUB CODE: MM, IE

NO REF SOV: 000

OTHER: 000

Card 2/2

DP

ITSKOVICH, A.A., inzh.

Shear testing by torsion of welded and glued and welded spot joints.
Svar. proizvod. no.9:35-36 S '65. (MIRA 18:9)

1. Tsentral'nyy nauchno-issledovatel'skiy institut stroitel'nykh
konstruktsiy im. V.A.Kucherenko Gosstroya SSSR.

LEONOVICH, A.A., inzh.; RUBANOVICH, B.B.; inzh.; SHVAKHUNOV, V.A., inzh.

Welded glue joints in structural elements. From. stroit. 42 no. 68
35-38 '65 (MIRA 18:15)

1. Tsentral'nyy nauchno-issledovatel'skiy institut stroitel'nykh
konstruktsiy Gosstroya SSSR.

NABIYEV, M.N., akademik; ZAKHZEVSAYA, A.V.; ITSKOVICH, A.M.

Crystallization of a complex nitric-phosphate fertilizer. Uzb.
khim. zhur. no.1:3-10 '61. (MIRA 14:1)

1. Institut khimii AN UzSSR. 2. Akademiya nauk UzSSR (for Nabiyev).
(Fertilizers and manures)

SERGOVANTSEV, V.T., kand.tekhn.nauk; YURASOV, V.V., kand.tekhn.nauk;
 ALUKER, Sh.M., kand.tekhn.nauk; ANDRIANOV, V.N., doktor tekhn.
 nauk; ASTAF'YEV, N.N., kand.tekhn.nauk; BUDZKO, I.A., akademik;
 BYSTRITSKIY, D.N., kand.tekhn.nauk; VEYALIS, B.S., kand.tekhn.
 nauk; GIRSHBERG, V.V., inzh.; GORSHKOV, Ye.M., inzh.; GRI-
 CHEVSKIY, E.Ya., inzh.; ZAKHARIN, A.G., doktor tekhn.nauk;
 ZLATKOVSKIY, A.P., kand.tekhn.nauk; IOSIPYAN, S.G., inzh.;
 ITSEKOVICH, A.M., dotsent; KAUFMAN, B.M., inzh.; KVITKO, M.N.,
 inzh.; KORSHUNOV, A.P., inzh.; LEVIN, M.S., kand.tekhn.nauk;
 LOBANOV, V.N., dotsent; LITVINENKO, A.F., inzh.; MERKULOV,
 G.F., inzh.; PIRKHAVKA, P.Ya., kand.tekhn.nauk; PRONNIKOVA,
 M.I., kand.tekhn.nauk; SMIRNOV, B.V., kand.tekhn.nauk; PATYU-
 SHENKO, S.G., inzh.; KHODNEV, V.V., inzh.; SHCHATS, Ye.L.,
 kand.tekhn.nauk; EBIN, L.Ye., doktor tekhn.nauk; BNTIN, I.A.,
 kand.tekhn.nauk; SILIN, V.S., red.; SMELYANSKIY, V.A., red.;
 BALLOD, A.I., tekhn.red.; SMIRNOVA, Ye.A., tekhn.red.

[Handbook pertaining to the production and distribution of
 electricity in agriculture] Spravochnik po proizvodstvu i
 raspredeleniiu elektricheskoi energii v sel'skom khoziaistve.
 Moskva, Gos.isd-vo sel'khoz.lit-ry, 1959. 900 p. (MIRA 13:2)

1.Vsesoyuznaya akademiya sel'skokhozyaystvennykh nauk imeni
 V.I.Lenina (for Budsko).
 (Rural electrification)

ITSKOVICH, Aleksandr Mikhaylovich; YEGORKINA, L.I., redaktor; MATVEYEVA, Ye.N.,
tekhnicheskii redaktor; EL'KIND, V.D., tekhnicheskii redaktor

[Technical thermodynamics] Tekhnicheskaya termodinamika. Moskva,
Gos.nauchno-tekhn.izd-vo mashinostroit.lit-ry, 1957. 191 p.
(Thermodynamics) (MIRA 10:7)

ITSKOVICH, Aleksandr Mikhaylovich, BAUMAN, I.M., red.; TIKHANOV, A.Ya.
tekhn.red.

[Low-pressure boiler installations] Kotel'nye ustanovki maloi
moshchnosti. Moskva, Gos.nauchno-tekhn. izd-vo mashinostroit.
lit-ry, 1958. 226 p. (MIRA 11:8)
(Boilers)

KAMINSKIY, D.M., kand. tekhn. nauk; MYL'NIKOV, V.A., inzh.; ITSKOVICH,
A.M., inzh.; BURLAK, S.T., inzh.; LEONT'YEV, F.Ye., inzh.

Use of semiconductor rectifiers in underground traction
substations. Izv. vys. ucheb. zav.; gor. zhur. 6 no.8:180-
182 '63. (MIRA 16:10)

1. Sibirskiy metallurgicheskiy institut (for Kaminskiy, Myl'nikov,
Itskovich).

ITSKOVICH, F.I. inzhener; LOSHCINSKAYA, A.V., inzhener; MIKHAYLOV,
S.P., inzhener.

Gas sampling device for QND-49 and QNUK-21 gas analysers.
TSement 22 no.3:17-19 My-Je '56. (MLRA 9:8)
(Gases--Analysis) (Waste products)

SOV/112-58-2-2512

, Translation from: Referativnyy zhurnal, Elektrotekhnika, 1958, Nr 2,
pp 115-116 (USSR)

AUTHOR: Itskovich, E. L.

TITLE: A Thermomagnetic Oxygen Gas Analyzer
(Termomagnitnyy gasoanalizator na kislород)

PERIODICAL: V sb.: Teploenerg. pribory i regulatory, M.-L., Mashgiz, 1956,
pp 195-201

ABSTRACT: An instrument for measuring the oxygen concentration in flue gases is described. It is designed on the principle of thermomagnetic convection. The instrument comprises a receiver, a gas sampler, and a supply pack consisting of a ferroresonance stabilizer with a selenium rectifier and a barretter. The receiver consists of a thermostatic section which houses a magnetic system and a measuring chamber. The measuring chamber includes four identical tungsten 30-micron wire heaters wound on a mica plate. To stabilize the sensitive elements, and to protect them against any aggressive influence of the gas, the heater winding is covered with a thin layer of glass by a hot-pressing

Card 1/2

SOY/112-58-2-2512

A Thermomagnetic Oxygen Gas Analyzer

method. All four heaters are connected in a Wheatstone bridge circuit, two opposite arms being located directly under the magnetic poles, and the two other arms being located in identical geometrical situations outside the magnetic field. Such a heater arrangement permits canceling the influence of the receiver slope upon the instrument reading. A 17-mv electron potentiometer with a scale calibrated in oxygen percentage serves as the measuring instrument of the gas analyzer. Scale zero checking and setting are done with a built-in millivoltmeter. To obtain a no-oxygen gas mixture, the gas being analyzed is passed through an electric furnace with fine-grained charcoal. The few instruments constructed have the following characteristics: measurement range 0 to 5% O_2 ; permissible zero uncertainty 0.2% O_2 ; main error 5% of the range, or 0.25% O_2 . A gas sampler secures normal operation of the instrument with the following gas parameters at the sampling point: temperature 150°-600° C; dust content up to 50 g/m³; rarefaction up to 130 mm of water column.

L.V.I.

Card 2/2

ITSKOVICH, E.L.

101-4-1/13

SUBJECT: USSR/Automatic Control

AUTHOR: Itskovich, E.L., Engineer

TITLE: Automatic Control of Gas-Heated Rotary Kilns (Avtomaticheskoye regulirovaniye vrashayushcheyssya pechi, rabotayushchey na gazoobraznom toplive)

PERIODICAL: Izvestiya, 1957, # 4, pp 1-10 (USSR)

ABSTRACT: A method for the construction of an automatic control system for rotary kilns was designed and approved by the Laboratories for Automation of Thermal Processes "TsPKBA" of the "SOYUZTEPLOKONTROL". The main task was to keep the output parameters within pre-set limits, and to maintain constant burning temperatures and constant feeding of the kiln. Indirect indicators were designed by special experiments for the technological output parameters. The indirect indications are measured with the following automatic devices: oxygen contents in the exhaust gases by means of a "TMRK-5" thermomagnetic gas analyzer; temperature of the exhaust gases - by thermocouples; the weight of 1 liter of clinker of a certain fraction - by a special automatic device which takes samples every 5 minutes, or scales equipped with an induction

APPROVED FOR RELEASE: 08/10/2001

CIA-RDP86-00513R000618920011-3"

101-4-1/13

TITLE:

Automatic Control of Gas-Heated Rotary Kilns (Avtomaticheskoye regulirovaniye vrachayushcheyssya pechi, rabotayushchey na gasoobraznom toplive)

transmitter. The experiments have shown that all control measures affect all, or the majority of parameters simultaneously and in approximately equal intensity. One of the output parameters - indicating the quality of clinkers - has such a delayed action (30 min) that a direct incorporation into the control system is not possible. The aforementioned properties required to find intermediate parameters, as well as complicated outside connections between the control systems. In order to facilitate this task, the work was approached in 2 stages:

1. Automatic stabilization of the operation of the furnace;
2. Automatic maintenance of output parameters within the set limits, and stabilizing them on the new level until arrival of the corrective impulse. Experiments lead to the conclusion that the stabilization operations of a rotary kiln should be based on those parameters which govern the burning of clinkers, and not on the stabilization of thermo-technical parameters which do not directly influence the technological process. Flow charts were designed to control the speed of kiln rotation

Card 2/4

101-4-1/13

TITLE:

Automatic Control of Gas-Heated Rotary Kilns (Avtomaticheskoye regulirovaniye vrashayushcheysya pechi, rabotayushchey na gazoobraznom toplive)

under simultaneous synchronisation of the burning temperature with the speed of feeding. The quality of the flow chart can be gauged by changes occurring in output parameters, since the first stage of the work is the reduction of such vacillations in these parameters. The fundamental requirements for the control system were:

1. Reduced interference with the control process of the kiln.
2. Changing of an output parameter to the standard of range has to be performed in such a way as to effect only minor value changes in the other parameters. Tests conducted in the Lenin-grad Cement Factory in Aug 56 proved the efficient automatic control of output parameters, i.e. the control actions remained within the intended limits.

The article contains 1 table, 3 figures, 3 diagrams. There are 15 references, 3 of which are Slavic (Russian)

Card 3/4

101-4-1/13

TITLE: Automatic Control of Gas-Heated Rotary Kilns (Avtomaticheskoye regulirovaniye vrashayushcheyaya pechi, rabotayushchey na gazobraznom toplive)

INSTITUTION: Laboratories for Automation of Thermic Processes of the Trust "SOYUZTEPLOKONTROL"

PRESENTED BY:

SUBMITTED:

AVAILABLE: At the Library of Congress

Card 4/4

5

The following is a list of the names of the persons who have been identified as having been involved in the activities of the Central Intelligence Agency (CIA) in the United States and abroad, as of the date of the release of this information.

1. [Name] [Address] [City] [State] [Zip]

2. [Name] [Address] [City] [State] [Zip]

3. [Name] [Address] [City] [State] [Zip]

4. [Name] [Address] [City] [State] [Zip]

5. [Name] [Address] [City] [State] [Zip]

6. [Name] [Address] [City] [State] [Zip]

7. [Name] [Address] [City] [State] [Zip]

8. [Name] [Address] [City] [State] [Zip]

9. [Name] [Address] [City] [State] [Zip]

10. [Name] [Address] [City] [State] [Zip]

11. [Name] [Address] [City] [State] [Zip]

12. [Name] [Address] [City] [State] [Zip]

13. [Name] [Address] [City] [State] [Zip]

14. [Name] [Address] [City] [State] [Zip]

15. [Name] [Address] [City] [State] [Zip]

16. [Name] [Address] [City] [State] [Zip]

17. [Name] [Address] [City] [State] [Zip]

18. [Name] [Address] [City] [State] [Zip]

19. [Name] [Address] [City] [State] [Zip]

20. [Name] [Address] [City] [State] [Zip]

21. [Name] [Address] [City] [State] [Zip]

22. [Name] [Address] [City] [State] [Zip]

23. [Name] [Address] [City] [State] [Zip]

24. [Name] [Address] [City] [State] [Zip]

25. [Name] [Address] [City] [State] [Zip]

26. [Name] [Address] [City] [State] [Zip]

27. [Name] [Address] [City] [State] [Zip]

28. [Name] [Address] [City] [State] [Zip]

29. [Name] [Address] [City] [State] [Zip]

30. [Name] [Address] [City] [State] [Zip]

31. [Name] [Address] [City] [State] [Zip]

32. [Name] [Address] [City] [State] [Zip]

33. [Name] [Address] [City] [State] [Zip]

34. [Name] [Address] [City] [State] [Zip]

35. [Name] [Address] [City] [State] [Zip]

36. [Name] [Address] [City] [State] [Zip]

37. [Name] [Address] [City] [State] [Zip]

38. [Name] [Address] [City] [State] [Zip]

39. [Name] [Address] [City] [State] [Zip]

40. [Name] [Address] [City] [State] [Zip]

41. [Name] [Address] [City] [State] [Zip]

42. [Name] [Address] [City] [State] [Zip]

43. [Name] [Address] [City] [State] [Zip]

44. [Name] [Address] [City] [State] [Zip]

45. [Name] [Address] [City] [State] [Zip]

46. [Name] [Address] [City] [State] [Zip]

47. [Name] [Address] [City] [State] [Zip]

48. [Name] [Address] [City] [State] [Zip]

49. [Name] [Address] [City] [State] [Zip]

50. [Name] [Address] [City] [State] [Zip]

51. [Name] [Address] [City] [State] [Zip]

52. [Name] [Address] [City] [State] [Zip]

53. [Name] [Address] [City] [State] [Zip]

54. [Name] [Address] [City] [State] [Zip]

55. [Name] [Address] [City] [State] [Zip]

56. [Name] [Address] [City] [State] [Zip]

57. [Name] [Address] [City] [State] [Zip]

58. [Name] [Address] [City] [State] [Zip]

59. [Name] [Address] [City] [State] [Zip]

60. [Name] [Address] [City] [State] [Zip]

61. [Name] [Address] [City] [State] [Zip]

62. [Name] [Address] [City] [State] [Zip]

63. [Name] [Address] [City] [State] [Zip]

64. [Name] [Address] [City] [State] [Zip]

65. [Name] [Address] [City] [State] [Zip]

66. [Name] [Address] [City] [State] [Zip]

67. [Name] [Address] [City] [State] [Zip]

68. [Name] [Address] [City] [State] [Zip]

69. [Name] [Address] [City] [State] [Zip]

70. [Name] [Address] [City] [State] [Zip]

71. [Name] [Address] [City] [State] [Zip]

72. [Name] [Address] [City] [State] [Zip]

73. [Name] [Address] [City] [State] [Zip]

74. [Name] [Address] [City] [State] [Zip]

75. [Name] [Address] [City] [State] [Zip]

76. [Name] [Address] [City] [State] [Zip]

77. [Name] [Address] [City] [State] [Zip]

78. [Name] [Address] [City] [State] [Zip]

79. [Name] [Address] [City] [State] [Zip]

80. [Name] [Address] [City] [State] [Zip]

81. [Name] [Address] [City] [State] [Zip]

82. [Name] [Address] [City] [State] [Zip]

83. [Name] [Address] [City] [State] [Zip]

84. [Name] [Address] [City] [State] [Zip]

85. [Name] [Address] [City] [State] [Zip]

86. [Name] [Address] [City] [State] [Zip]

87. [Name] [Address] [City] [State] [Zip]

88. [Name] [Address] [City] [State] [Zip]

89. [Name] [Address] [City] [State] [Zip]

90. [Name] [Address] [City] [State] [Zip]

91. [Name] [Address] [City] [State] [Zip]

92. [Name] [Address] [City] [State] [Zip]

93. [Name] [Address] [City] [State] [Zip]

94. [Name] [Address] [City] [State] [Zip]

95. [Name] [Address] [City] [State] [Zip]

96. [Name] [Address] [City] [State] [Zip]

97. [Name] [Address] [City] [State] [Zip]

98. [Name] [Address] [City] [State] [Zip]

99. [Name] [Address] [City] [State] [Zip]

100. [Name] [Address] [City] [State] [Zip]

"APPROVED FOR RELEASE: 08/10/2001

CIA-RDP86-00513R000618920011-3

with the help of cement plants, proved that it gave depend-
able results.

W. H. Slaughter

2K

APPROVED FOR RELEASE: 08/10/2001

CIA-RDP86-00513R000618920011-3"

1 15000-14, 15000-15

AUTHORS Ageykin D.I., Itskovich E.L., Vorob'yev I.N. (Deceased) 32-7-29/49
TITLE New Construction of a Thermomagnetic Gas Analyzer Based Upon Oxygen.
(Novaya Konstruktsiya termomagnitnogo gazoanalizatora na kislorod-
-Russian)
PERIODICAL Zavodskaya Laboratoriya, 1957, Vol 23, Nr 7, pp 852-858 (U.S.S.R.)
ABSTRACT This device consists of a principal component (indicator) in which measuring of thermal magnetic convection is carried out, the electric elements being fitted to the interior of the lid. Inside there is a thermostatic cell with a magnetic system and measuring chamber with sensitive elements through which the gas to be analyzed passes. The device has a permanent magnet (made of "magniko" alloy), the magnetic conductor is made of "armko" iron, and the pole points made of "permendur" serve for the maintenance of a maximum field voltage. The magnetic system has "gabarites" having a great stability of magnetic field voltage as well as a hermetically closed chamber the interior of which is coated with lead. The indicator possesses two sensitive elements in the measuring chamber each having two heaters as extensions of the magnetic bridge. Here the position of the sensitive elements as well as that of the heater are fixed in proportion to the magnetic pole. By an increase of the oxygen content of the gas mixture thermomagnetic convection is increased. By means of this device it is thus possible to determine the number of oxygen molecules in the gas volume unit of the measuring chamber. In this way also partial pressure is determined.

Card 1/2

New Construction of a Thermomagnetic Gas Analyzer 32-7-29/49
Based Upon Oxygen.

There are no Illustrations.

ASSOCIATION Institute of Automation and Telemechanics, AN USSR.
(Institut avtomatiki i telemekhaniki Akademii nauk SSSR.)
AVAILABLE 3 Library of Congress.

Card 2/2

ITSKOVICH, E. L.: Master Tech Sci (diss) -- "Synthesis of a system of automatic regulation of the process of roasting cement clinker in a rotary furnace using gaseous fuel". Moscow, 1958. 17 pp (Acad Sci USSR, Inst of Automatics and Telemechanics), 185 copies (KL, No 4, 1959, 126)

ITSKOVICH, Emmanuil L'vovich, LOSHCINSKAYA, Anna Valer'yanovna,; LECHTENKOV,
A.I., nauchnyy red.; TYUTYUNIK, M.S., red.; GILSON, P.G., tekhn. red.

[Automatic control in the burning of cement clinker] Avtomaticheskii
kontrol' obshchego tsementnogo klinkera. Moskva, Gos. izd-vo lit-ry
po stroit., arkhitekt. i stroit. materialam, 1958. 48 p. (MIRA 11:10)
(Cement kilns)
(Automatic control)

AUTHORS: Itskovich, E. L. and Ioshchinskaya, A. V. 101-58-3-2/12

TITLE: Graduation of Gas Analyzers on CO₂ Based on the Measurement of Heat Conductivity of the Mixture, ²for Rotary Furnaces
(Gradnirovka gazoanalizatorov na CO₂, osnovannykh na izmerenii teploprovodnosti smesi, dlya vrashchayushcheyasya pechi)

PERIODICAL: Tsement, 1958, ²⁴Nr 3, pp 1-6 (USSR)

ABSTRACT: The article deals with the use of electrical gas analyzers of the GED-49 and GEUK-21 type to analyze waste gases from cement roasting rotary furnaces. They operate on the basis of measuring the heat conductivity of gas mixtures and require an adjustment in the graduation if used for determining the CO₂ content in waste gases from rotary furnaces. To carry out such alterations, a testing arrangement is recommended as shown in diagram 4. There are 2 diagrams, 1 table, 2 graphs and 1 Soviet reference.

Card 1/1 1. Gas--Waste--Analysis 2. Gas analyzers--Applications 3. Gas analyzers--Operation

15(6)

SOV/101-59-2-3/13

AUTHOR: Itskovich, E.L.

TITLE: Automatic Control of the Specific Heat Consumption for the
Calcination Process in the Rotary Kiln

PERIODICAL: Tsement, 1959, Nr 2, pp 6-12 (USSR)

ABSTRACT: The author states that an automatic computation device has been designed, to show the amount of the specific fuel consumption at any desired moment. Practical adaptation of such a device at the rotary kiln will permit the optimum operating conditions of the working kiln. The author also states that the instantaneous heat consumption can also be estimated by means of an analysis of the escaping gases. For this purpose, the gases undergo a splitting into their components, such as oxygen, carbonic acid and combustion constituents. Calculation of the specific consumption of heat, based on the characteristics of raw material, fuel, process conditions, and analysis of escaping gases, are presented in a book written by Ye. I. Khodorov, "Pechi

Card 1/5

SOV/101-59-2-3/13

Automatic Control of the Specific Heat Consumption for the Calcination Process in the Rotary Kiln

tsementnoy promyshlennosti", Ch. II. ("Furnaces of the cement industry", part II). The author quotes the basic equation of combustion, occurring under conditions of an incomplete burning and excess of air:

$$\text{CO}_2^T + \mu \text{CO}^T + \text{O}_2^T = 20.9 - \beta \text{CO}_2^T \quad (1)$$

where CO_2^T , CO^T and O_2^T are the components of smoke gas of any fuel, and β are the carbon-dioxide characteristics.

The author reproduces in sequence, the full chemical calculation, illustrating the continuity of the combustion process. The above calculation contains several variable coefficients, the value of which depends upon the actual production conditions. In connection with such unavoidable irregularity, the author refers to the methodical errors due to the oscillations in the coefficient values

Card 2/5

SOV/101-59-2-3/13

Automatic Control of the Specific Heat Consumption for the Calcination Process in the Rotary Kiln

determined at the Novorossiyskiy tsementnyy zavod "Oktyabr'" (Novorossiysk Cement Plant "Oktyabr'") and at the Leningradskiy tsementnyy zavod (Leningrad Cement Plant) employing Stavropol' gas of a stable composition, and artificial shale gas of a variable consistency. Figure 1 shows the recalculation graph giving the correction factor for the definition of "q", which symbolizes the specific heat consumption. This calculation is also valid for kilns on powdered coal fuel. But, in this case, the correctness of the calculation will suffer due to the inconsistency of this fuel. On the basis of the above method, an automatic computer has been designed, producing continuously mathematic calculations relating to the concentration of components of the escaping gases, such as O_2 , CO_2 and CO . Figure 2 shows the basic scheme of the computing device, giving the specific consumption of fuel

Card 3/5

SOV/101-59-2-3/13

Automatic Control of the Specific Heat Consumption for the Calcination Process in the Rotary Kiln

for the calcination purposes. The device consists of four types of "EPD" or "EPV" electron potentiometers. Three of them are secondary devices, corresponding to the gas analyzers, and show values of O_2 , CO_2 and CO , in the escaping gases, and the fourth directly indicates the specific consumption of heat used for calcination purposes. The resistor-type transmitters R_1 , R_2'' , R_2''' , and R_4 , connected into the electric bridge, change their resistances in proportion to the position of the hand of the corresponding potentiometer, i.e. in proportion to the concentration of the definite component of the escaping gases. Calculation of the full resistances of all resistor-type transmitters permits to determine all coefficients of the proportionality. In the capacity of transmitters - the automatic gas analyzers may also be used, indicating O_2 , CO_2 and CO H_2 , adapted in the installation of the UGT-2

Card 4/5

SOV/101-59-2-3/13

Automatic Control of the Specific Heat Consumption for the Calcination Process in the Rotary Kiln

(Ural Geological Trust-2), issued by the "Sevzapmontazh-avtomatika" for the rotary kilns. The laboratory for automatization of thermal processes "SPKBA" of the "Sevzapmontazhavtomatika" trust has performed comparative experiments with one rotary kiln at the Leningrad Cement Plant. Comparison between the amounts of specific fuel consumption, obtained by a direct measurement of the consumed gas fuel and weight of the produced clinker, and the amount calculated from the indications, is given by the gas analyzers, in the installation of the Ural Geological Trust-2. Figure 3 shows part of the obtained registration. The author concludes that the use of the apparatus for a continuous indication of the specific consumption of heat for calcination, with a degree of correctness of 6%, will help in the appreciation of the economical factors, influencing the process of calcination and of the process itself. There are 2 graphs and 1 diagram.

Card 5/5

15(6)

AUTHOR:

SOV/119-59-10-1/19
Itskovich, E. L., Candidate of Technical Sciences

TITLE:

A Synthesis of the Automatic Control Circuit of a Rotary Cement Kiln

PERIODICAL:

Priborostroyeniye, 1959, Nr 10, pp 1-6 (USSR)

ABSTRACT:

In the introduction, the dimensions of rotary kilns with recuperative coolers intended for the burning of cement clinker are presented. These kilns operate by the "wet" method. Accordingly, the cylinders are 2.5-4 m wide, 40-150 m long, their inclination is 3-5°, and they usually rotate with 1 rpm. The charge passes from the cold to the hot end within 2.5-4 h. The furnace gases flow in a direction opposite to that of the charge. Further, details of the air current in the furnace and recuperator are given. The individual zones in which the various physical and chemical variations of the material take place, are also discussed. The author indicates that it is necessary to maintain the charge at certain temperatures to guarantee first quality of the furnace products. All processes in the furnace are controlled by five devices: 1) One for regulating heat consumption; 2) one for regulating the consumption of primary air; 3) a speed-regulating device;

Card 1/3

SOV/119-59-10-1/19

A Synthesis of the Automatic Control Circuit of a Rotary Cement Kiln

4) one for regulating slime consumption; 5) one for regulating the consumption of secondary air. No precise automatic control of the motions within the furnace and no data on the influence exercised by the various factors upon the mode of operation of the heat zones have been made available as yet for design. The characteristic mode of operation of the individual unit parts was indirectly investigated by experiments in which the discharge data and temperature conditions in the furnace were determined by means of numerous temperature indicators. The experiments were made by the Laboratory for Automation of Thermal Processes of the "Svzapsmontavtomatika" Trust on Industry Furnace Nr 2 of the Leningradskiy tsementnyy zavod imeni Vorovskogo (Leningrad Cement Factory imeni Vorovskiy). The static and dynamic properties of the main items are summarized in table 1. The variation of these items with time appears to be a steady and ergodic random function if the items variations in normal operation occur within certain limits. This allows for the estimation of the eigenfunction and the intercorrelation function of the items. Herefrom it followed that the weight per liter of clinker cannot be regulated by changing the supply of heat. From the further investigation

Card 2/3

SOV/119-59-10-1/19
A Synthesis of the Automatic Control Circuit of a Rotary Cement Kiln

the author concluded that the weight per liter of clinker can be regulated by changing the temperature within the zone of clinkering. A control device designed for this purpose guarantees the required quality of clinker, as shown by experiments. It proved to be necessary to stabilize the wetness at the end of the drying zone. This was attained by regulating the temperature of the emanating gases. The temperature of the emanating gases was regulated by changing the supply of secondary air. The oxygen content of these gases is regulated by changing the supply of heat and secondary air. In conclusion, the author discusses the consequences resulting from a variation in the number of revolutions and primary air supply. The control circuit developed here was realized in the form of a universal regulator in the rotary furnace mentioned in the introduction. Experiments have proved the exactness of the method of synthesis of a control circuit applied here. There are 6 figures and 1 table.

Card 3/3

PHASE I BOOK EXPLOITATION

SOV/5528

Drabkin, G. S., I. P. Brovar, Ya. Ye. Gel'fand, and E. L. Itskovich

Avtomatizatsiya tsementnykh zavodov. (Automation of Cement Plants)
Leningrad, Gosstroyizdat, 1961. 399 p. Errata slip inserted.
4,000 copies printed.

Scientific Ed.: A. I. Leontenkov, Engineer; Ed. of Publishing
House: A. S. Rotenberg; Tech. Ed.: L. V. Voronetskaya.

PURPOSE: This book is intended for technical personnel of cement
plants and design and planning offices.

COVERAGE: Descriptions are given of the technical characteristics
of instruments, devices, and circuits of automatic monitoring,
control, and regulation systems used in manufacturing processes
at cement plants. Prospects for the development of complex auto-
mation of the main manufacturing processes in cement plants are
reviewed. Chs. I, III, VI-IX, and XIV were written by I. P.
Brovar and G. S. Drabkin; Chs. II, V, and X-XII, by Ya. Ye.
Gel'fand; and Chs. IV, XIII, and Sec. 16 of Ch. V, by E. L.

Card ~~1/8~~

Automation of Cement Plants

SOV/5528

Tsikovich. There are 30 references: 27 Soviet (including 1 translation), 2 English, and 1 German.

TABLE OF CONTENTS:

Foreword	3
Introduction	5
Ch. I. Pressure Measurement	9
1. Equipment for measuring pressure and rarefaction	9
2. Pressure indicators	21
Ch. II. Flow Measurement	23
3. Flow measurement of liquids and gases	23
4. Flow measurement of slime and other viscous and impure liquids	25
5. Flow measurement of lump and powderlike materials	28

Card ~~2~~/8

16.9500(1031, 1121, 1132)

S/103/61/022/002/007/015
B019/B060

AUTHOR: Itskovich, E. L. (Moscow)

TITLE: Determination of necessary repetitions of measurements in discrete controls

PERIODICAL: Avtomatika i telemekhanika, v. 22, no. 2, 1961, 216-223

TEXT: In studies having the purpose of automatizing technical objects the determination of the frequency at which certain quantities are measured plays an important part. At first, the results of some laboratory measurements under different operational conditions will be the only data available. In the study made here the quantities to be controlled are assumed to be continuous random functions of time. All such functions as characterize continuous processes in technical objects practically belong to this class of quantities. In the author's opinion, the following factors should be taken into account when determining the frequency of measurements in the control of technical processes: 1) Initial data for the solution of the problem concerned should be available. These initial data can be obtained by continuous recording and determination of the mean

Card 1/3

89176

Determination of necessary ...

S/103/61/022/002/007/015
B019/B060

values in suitable time intervals. 2) The character of the function which is used for the approximation of a steadily changing quantity. In most cases, this will be a step function, and the approximation error must be taken into account when selecting the necessary frequency of measurements. 3) The demands made as to the accuracy of measurements must be taken into account. Such demands depend upon the type of effect a change of the quantities has upon the course of the process in the object. It is shown that the measured quantities can be classified into two groups according to the demands made as to their accuracy. The error of the measured quantities of the first group must not at any instant exceed a certain given value. A mean square error is given for the measured quantities of the other group. In the discrete control of quantities belonging to the first group the accuracy of measurements can be determined as follows: (a) If the spectral density of the quantity to be controlled is known, the accuracy of measurement can be determined by:

$$N_1 \leq \omega_0 |y_{\max}(t)| / (\delta - \delta_0) \quad (7)$$

Card 2/3

89176

S/103/61/022/002/007/015

B019/B060

Determination of necessary ...

Here, N_1 denotes the frequency of measurement, ω_0 is the frequency of the cross section of the spectral density $y(t)$, δ is the admissible error of measurement, and δ_{η} is the instrumental error. In the absence of initial data it is necessary to carry out specific tests in which the changes taking place with time in the quantities to be controlled are studied. In the discrete control of quantities belonging to the second group the accuracy of measurements will be determined from: (a) if the correlation functions of the functions to be controlled are known, by formula $N_2 = 1/h_2$ (10), where h_2 is the time between two adjoining measurements and is determined with the correlation functions. (b) if initial data are not available, it will be necessary here as well to make an analysis of specific measurement values. S. N. Bernshteyn and V. N. Khlistunov are mentioned. There are 4 figures, 1 table, and 2 Soviet-bloc references. X

SUBMITTED: July 11, 1960

Card 3/3

ITSKOVICH, E.L.

Main trends in the automation of cement manufacture. TSement 28
no.2:8-10 Mr-Ap '62. (MIRA 15:8)

1. Institut avtomatiki i telemekhaniki AN SSSR.
(Cement industries) (Automatic control)

S/103/63/024/002/012/020
D201/0308

916100

AUTHOR: Itskovich, E.I. (Moscow)
TITLE: Determination of pick-up spacing in the control of space distributed fields
PERIODICAL: Avtomatika i telemekhanika, v. 24, no. 2, 1963, 233-239

13

TEXT: The author considers the problem of automatic determination of the magnitude of a field at any required point by using the least possible number of pick-up. The above problem and that of determining the pick-up spacing is considered for the case of control of a field distributed linearly along one coordinate only. The allowable rms measurement error in the field distribution is assumed to be known, the distribution of the field is assumed to be random. The procedure in determining the field consists in determining the statistical field characteristics i.e. in analyzing the random function of the distribution of the given quantity along the given coordinate, the length of the latter being limited by the

Card 1/2

ITSKOVICH, Emmanuil L'vovich; TEYMAN, A.I., red.

[Statistical methods in production automation] Statisticheskie metody pri avtomatizatsii proizvodstva. Moskva, Izd-vo "Energia," 1964. 189 p. (MIRA 17:6)

ITSKOVICH, E.L.; KONDAKOV, V.F.

Using the model of transient responses in evaluating the object
by the recording of values in the process of a regular operation
of the unit. Priborostroenie no.7:5-8 J1 '64.

(MIRA 17:11)

TEREKHOV, E.I. (Moskva)

Calculation of the cumulative indices of production performance of an
automatic control system. Avtom. i tekm. 26 no. 7:1253-1264 61 '65.
(MIRA 18:6)

CHELYUSTKIN, A.B., red.; ITSKOVICH, E.L., red.; PLISKIN, L.G.,
red.; RAYMAN, N.S., red.; CHERNYSHEV, V.N., red.;
VOLKOV, V.L., red.; CHADEYEV, V.M., red.

[Automatic operational control of production processes;
transactions] Avtomaticheskoe operativnoe upravlenie pro-
izvodstvennymi protsessami; trudy. Moskva, Nauka, 1965.
244 p. (MIRA 18:11)

1. Vsesoyuznaya konferentsiya po avtomaticheskomu opera-
tivnomu upravleniyu proizvodstvennymi predpriyatiyami. Ist.
Moscow, 1963.

L 10377-67 EWP(k)/EWT(d)/EWP(h)/EWP(1)/EWP(v)

ACC NR: AP7003063

SOURCE CODE: UR/0103/66/000/008/0139/0148

AUTHOR: Itskovich, E. L. (Moscow); Trakhtengerts, E. A. (Moscow) 27

ORG: none

TITLE: Minimization of memory size for a program of centralized production control.
Part 1

SOURCE: Avtomatika i telemekhanika, no. 8, 1966, 139-148

TOPIC TAGS: algorithm, computer memory

ABSTRACT: The problem of compiling standard subroutines for realizing a centralized production control algorithm and determination of the volume of information to be processed by these subroutines is stated. A method is analyzed for determining the number of elementary operations required to run a standard subroutine. Orig. art. has: 13 formulas and 1 table. [JPRS: 38,836] ..

SUB CODE: 09 / SUBM DATE: 26Nov65 / ORIG REF: 004

Cord 1/1 JB

UDC: 681.142.352.4

Translation from: Referativnyy Zhurnal, Elektrotehnika, 1957, 112-3-5098
Nr 3, p. 5 (USSR)

AUTHORS: Lifshits, I.M., and Itskovich, F.I.

TITLE: The Kinetics of the Decay of Superconductivity Under
the Influence of an Alternating Field (O kinetike
razrusheniya sverkhprovodimosti peremennym polem)

PERIODICAL: Uch. zap. Khar'kovsk. un-ta, 1955, vol. 64, pp. 45-57

ABSTRACT: Bibliographic entry.

ASSOCIATION: Khar'kov University (Khar'kovsk. un-t)

Card 1/1

L 45101-66 EWT(1)/EWT(m)/EWP(w)/T/EWP(t)/ETI IJP(c) JD/AT

ACC NR: AP6024891

SOURCE CODE: UR/0056/66/051/001/0301/0308

AUTHOR: Itskovich, P. I. 80
B

ORG: Khar'kov Engineering School for Officers (Khar'kovskoye, vyssheye-komandno-inzhenernoye uchilishche)

TITLE: Effective work functions for different types of electron emission from metals 14

SOURCE: Zhurnal eksperimental'noy i teoreticheskoy fiziki, v. 51, no. 1, 1966, 301-308

TOPIC TAGS: work function, thermionic emission, photoeffect, thermionics, field emission, *ELECTRON EMISSION, PHOTOEFFECT*

ABSTRACT: It is shown that for an arbitrary electron dispersion law in metals the effective thermionic emission and surface photoeffect work functions (W_t and W_{ph}) reduced to a zero field may be larger than the true work function W . These quantities may differ from each other and also from the effective work function for field emission W_f . In such a case $W_{ph} \geq W_t \geq W$ and $W_{ph} \geq W_f \geq W$ (all quantities refer to a given single face). If the three reduced effective work functions are equal, they are almost certainly identical with W . The thermionic current for an arbitrary

Card 1/2

L 45101-66

ACC NR: AP6024891

dispersion law is also calculated. The experimental data as a whole are in accordance with the results obtained. Orig. art. has: 16 formulas and 3 figures.

SUB CODE: 20/ SUBM DATE: 15Feb66/ ORIG REF: 008/ OTH REF: 006

Card 2/2 blg

ISKOVICH, F.I.

AUTHOR:

ZIL'BERMAN, G.E., ISKOVICH, F.I.

PA - 2078

TITLE:

Temperature Dependence of the Magnetic Susceptibility of Electrons in Metals. (Temperaturnaja zavisimost' magnitnogo vospriimchivosti elektronov v metalle, Russian).

PERIODICAL:

Zhurnal Eksperimental'noi i Teoret.Fiziki, 1957, Vol 32, Nr 1, pp 158-160 (U.S.S.R.)

Received: 3 / 1957

Reviewed: 4 / 1957

ABSTRACT:

The authors investigated the temperature dependence of the magnetic susceptibility χ of electrons within a wide temperature interval in weak magnetic fields, when χ practically does not depend on H. Here the following cases are investigated:

- 1) Only small electron groups exist.
- 2) Furthermore, also great electron groups exist.
- 3) In addition, great hole groups exist.

Computations are carried out here on the assumption of a quadratic dispersion law, taking into account the spin-paramagnetism and the anisotropy of effective masses.

Hexagonal bismuth crystals are investigated (results in the case of other symmetry types remain qualitatively unchanged). Furthermore, as usual, the existence of three homogeneous small ellipsoid-like groups is assumed. The axes of these ellipsoids form angles of 120° in the plane of the binary axis.

Card 1/3

Temperature Dependence of the Magnetic Susceptibility of
Electrons in Metals. PA - 2078

Case I: For the components χ_1 (the index 3 here denotes the principal axis) of the 3 aforementioned groups computations furnish the expression:

$$\chi_1 = - (1/2) AB_1 (kT)^{1/2} F_{-1/2}(\xi/kT) = - AB_1 \sqrt{\xi} X.$$

Also the quantities occurring in this formula are given explicitly. For the dependence of the chemical potential ξ on temperature the following formula is obtained from the condition of constancy of the concentration n of electrons:

$\theta = [(3/2)F_{1/2}(u)]^{-2/3}$. After computation of the function $F_{+1/2}$, $X(\theta)$ is determined, i.e. the required dependence $\chi(T)$ in universal coordinates, and, furthermore, $\xi(\theta)/\xi_0$. For

limiting cases (extensive degeneration as well as validity of BOLTZMANN'S statistics) the following relations are found:

$$T \ll T_0: X = 1 - \pi^2 \theta^2 / 12, \quad \xi / \xi_0 = 1 - \pi^2 \theta^2 / 12,$$

$$T \gg T_0: X = 2/3 \theta, \quad \xi / \xi_0 = (3/2) \theta \ln[(16/9\pi)^{1/3} \theta^{-1}].$$

Card 2/3

PA - 2078
Temperature Dependence of the Magnetic Susceptibility of
Electrons in Metals.

The curves for $\chi(\theta)$ and $\chi(\theta)/\chi_0$ as well as for their
asymptotic expressions are demonstrated in a diagram. Such
a temperature dependence of χ applies in the very case of the
series of metals.
Case 2) and 3) are dealt with in a similar manner and the
equations obtained are given explicitly as under 1).

ASSOCIATION: Not given
PRESENTED BY:
SUBMITTED:
AVAILABLE: Library of Congress
Card 3/3

24.2120

68193

SOV/58-59-5-10999

Translation from: Referativnyy Zhurnal Fizika, 1959, Nr 5, p 156 (USSR)

AUTHORS: Zil'berman, G.Ye., Itskovich, F.I.

TITLE: On the Thermodynamics of an Electron Gas Under an Arbitrary Dispersion Law 21 21

PERIODICAL: Tr. Khar'kovsk. politekhn. in-ta, 1958, Vol 14, pp 133 - 140

ABSTRACT: The authors calculate some thermodynamic functions for the case of an arbitrary law of dispersion of the electrons in a metal. The crossover method adopted to calculate the statistical sums requires the fulfilment of conditions coinciding with the criteria of the quasi-classical description. For the square law of dispersion these conditions are strictly satisfied, but not, generally speaking, in the case of the arbitrary dispersion law; as a result the expressions obtained in this study bear an approximate character. The authors calculate the heat capacity of the electron gas in the presence of a magnetic field. That part of the heat capacity which depends on the magnetic field is connected with the concrete form of the dispersion law, while the part not dependent on the field is obtained for the arbitrary dispersion law. The heat

Card 1/2

68193

SOV/58-59-5-10999

On the Thermodynamics of an Electron Gas Under an Arbitrary Dispersion Law

capacity oscillates as a function of the magnetic field, but most of the oscillating terms mutually cancel out, whereas the corresponding terms in the expression for the magnetic moment are retained. Consequently the magnetic-field dependence of the heat capacity turns out to be a relatively weaker effect than the De Haas - van Alfvén effect.

A.A. Filyukov

Card 2/2

ITSKOVICH, F.I.

Effect of the quantization of the energy of particles in a finite
volume on the thermodynamic values of a Fermi gas. Izv.vys.ucheb.
zav.; fiz. no.2:13-23 '61. (MIRA 14:7)
(Electron gas) (Quantum statistics)

ACCESSION NR: AP4025924

S/0056/64/046/003/0913/0919

AUTHOR: Gogadze, G. A.; Itskovich, F. I.; Kulik, I. O.

TITLE: Quantum oscillations of cold-emission current of metals in a magnetic field

SOURCE: Zhurnal eksperimental'noy i teoreticheskoy fiziki, v. 46, no. 3, 1964, 913-919

TOPIC TAGS: cold emission, field emission, tunnel current, tunnel current oscillation, chemical potential, number of electronic states, complex cathode emission

ABSTRACT: Following an earlier study of the oscillations of the tunnel current between two metals separated by a thin layer of dielectric, which yielded a more accurate determination of the effective mass and which showed that the tunnel-current oscillations depend significantly on the oscillations of the chemical potential of the metals, the authors investigate theoretically the oscillations of the field-emission current from a metal in a magnetic field perpendicular to the sample surface. The oscillations are shown to be due either to oscillations

Card 1/2

ACCESSION NR: AP4025924

in the number of the electronic states in the magnetic field or to oscillations of the chemical potential of the metal, the latter having usually an appreciable amplitude and the former being significant only for metals having small electron groups. As an example, the features are considered of field emission from a complex cathode consisting of two metals separated by a thin layer of dielectric, through which tunnel current can flow. It is shown that a considerable current can exist even in a relatively weak field incapable of inducing appreciable emission from one of the metals (in the absence of a potential difference between metals). The field-emission current exhibits oscillations associated with both metals. It is pointed out that an experimental investigation of these oscillations is extremely difficult. Orig. art. has: 4 figures and 16 formulas.

ASSOCIATION: Fiziko-tekhnicheskiy institut nizkikh temperatur AN UkrSSR (Physicotechnical Institute of Low Temperatures, AN UkrSSR); Khar'kovskoye vy'sheye komandno-inzhenernoye uchilishche (Khar'kov Engineer Officers' College).

SUBMITTED: 27Jul63

DATE ACQ: 16Apr64

ENCL: 00

SUB CODE: PH, GE

NR REF SOV: 009

OTHER: 001

Card 2/2

L 34390-66 ENT(1)

ACC NR: AP6018823

SOURCE CODE: UR/0056/66/050/005/1425/1437

AUTHOR: Itskovich, F. I.

ORG: Kharkov Higher Command Engineering School (Khar'kovskoye
vyssheye komandno-inzhenernoye uchilishche)

TITLE: Theory of field emission from metals

SOURCE: Zh eksper i teor fiz, v. 50, no. 5, 1966, 1425-1437

TOPIC TAGS: metal crystal, free electron, electron emission, electron spectrum, field emission

ABSTRACT: The field emission from a metal single crystal has been investigated for an arbitrary electron dispersion law. The formula for the free electron theory holds true for the cold emission (accurate to a preexponential factor) if the Fermi surface is intersected by an axis p_z perpendicular to the emitting surface of the sample. Otherwise, the law of the tangential quasi-momentum of an electron emitted from the metal leads to the replacement of the work function w in the exponent by a larger quantity W . The distance between the Fermi surface and axis p_z can be estimated from the difference $W-w$, which yields definite information concerning the electron spectrum of the metal.

Card 1/2

L 34390-66

ACC NR: AP6018823

The author thanks I. M. Lifshits and M. Ya. Azbel for their discussions, and G. Ye. Zil'berman and I. O. Kulik for their interest in this work and valuable discussions. Orig. art. has: 8 figures and 21 formulas. [Based on author's abstract] [NT]

SUB CODE: 20/ SUBM DATE: 22Dec65/ ORIG REF: 003/ OTH REF: 003

Card 2/2

MITINSKIY, Arseniy Nikolayevich; MOVNIN, M.S. Prinimal uchastiye:
IZRAYELIT, A.B., ITSEKOVICH, G.M., inzh., nauchnyy red.;
SHAURAK, Ye.N., red.; LEVOCHKINA, L.I., tekhn.red.

[Strength of materials] Soprotivleniye materialov. Pod-
gotovleno k izdaniyu M.S.Movninym. Leningrad, Gos.soiuznoe
ind-vo sudostroitel.pr-myshl., 1959. 294 p. (MIRA 12:5)
(Strength of materials)

DARKOV, A.V., prof., doktor tekhn.nauk; MITROPOL'SKIY, N.M., prof.,
dokt.tekhn.nauk; SHPIRO, G.S., kand.tekhn.nauk; DIDOV, B.V., prof.,
retsensent; BYCHKOV, P.G., dotsent, retsensent; ITS KOVICH, G.M.,
nauchnyy red.; ANOSHINA, K.I., red.izd-va; TITOVA, L.L., tekhn.
red.

[Strength of materials] Soprotivlenie materialov. Moskva, Gos.
izd-vo "Vysshaya shkola," 1959. 741 p. (MIRA 13:4)
(Strength of materials)

KRAVCHENKO, Petr Yefimovich, kand.tekhn.nauk; MILOVIDOV, S.S., prof.,
retsensent; ITSEKOVICH, O.M., inzh., retsensent; RABINOVICH, S.V.,
red.; ANOSHINA, K.I., red.ind-va; SHLYK, M.D., tekhn.red.

[Fatigue strength] Ustalostnaya prochnost'. Moskva, Gos.ind-vo
"Vysshaya shkola." 1960. 103 p. (MIRA 13:5)
(Metals--Fatigue)

ITSKOVICH, Georgiy Meyerovich; MAKUSHIN, V.M., dotsent, kand.tekhn.nauk,
retsensent; LIZHANKOV, A.A., inzh., retsensent; RABINOVICH, S.V.,
dotsent, kand.tekhn.nauk, nauchnyy red.; LIPKINA, T.G., red.isd-va;
YEZHOVA, L.L., tekhn.red.

[Strength of materials] Soprotivleniye materialov. Moskva, Gos.
izd-vo "Vysshaya shkola," 1960. 529 p.

(MIRA 14:3)

(Strength of materials)

ITSKOVICH, Georgiy-Meyerovich; ARKUSHA, A.I., otv. za vypusk;
IGNATOVA, T.D., red.

[Methods of presenting the topic "Theories of strength" in
technical schools] Nekotorye voprosy metodiki izlozhenia ta-
my "Teorii prochnosti" v tekhnikumakh. Moskva, Upr. kadrov
i ucheb. zavedenii. Nauchno-metodicheskii kabinet, 1962. 31 p.
(MIRA 15:8)

(Strength of materials)

STOROZHEV, Nikolay Fedorovich; ITSKOVICH, G.M., red.; BELYAK, Yu.L.,
retsensent; KAN, P.M., red. izd-va; BODROVA, V.A., tekhn.
red.

[Elementary strength calculations of ship structures and
mechanisms] Elementarnye raschety prochnosti sudovykh kon-
struktsii i mekhanizmov; sbornik zadach. Moskva, Izd-vo
"Rechnoi transport," 1962. 260 p. (MIRA 15:11)
(Naval architecture--Problems, exercises, etc.)

ITSKOVICH, Georgiy Meyerovich; VINOKUROV, Anatoliy Ivanovich;
ROZANOVA, G.K., red.izd-va; GOROKHOVA, S.S., tekhn.red.

[Strangth of materials; program and test problems with
brief methodological instructions for their completion]
Soprotivlenie materialov; programma i zadaniia dlia kont-
rol'nykh rabot s kratkimi metodicheskimi ukazaniiami po
ikh vypolneniiu. Metodicheskoe posobie dlia uchashchikh-
sia mashinostroitel'nykh spetsial'nostei zaachnykh tekhn-
ikumov na baza 7 i 10 klassov. Izd.7, perer. Moskva,
Vysshiaia shkola, 1963. 76 p. (MIRA 17:1)

1. Russia (1923- U.S.S.R.) Ministerstvo vysshego i sred-
nego spetsial'nogo obrazovaniya.
(Strength of materials)

SLIVCHANSKAYA, V.V.; ITSKOVICH, G.M.; SAUTKIN, N.I.

Characteristics of the structure of a continuous ingot of low-carbon rimmed steel. Stal' 24 no.2:128-131 F '64.

(MIRA 17:9)

1. Tsentral'nyy nauchno-issledovatel'skiy institut chernoy metallurgii imeni I.P. Bardina.

DARKOV, Anatoliy Vladimirovich, prof., doktor tekhn. nauk; SUIERO,
Geyman Simonovich, kand. tekhn. nauk; Prinimal uchastiye
ITSKOVICH, G.M., inzh.

[Strength of materials] Soprotivlenie materialov. Moskva,
Vysshaya shkola, 1965. 762 p. (MIRA 18:2)

OBODOVSKIY, Boris Arnol'dovich; KHANIN, Solomon Yefimovich;
Prinimali uchastiye ORZHEKHOVSKAYA, O.P.; ITSKOVICH,
G.M.; DARKOV, A.V., prof., doktor tekhn. nauk.
retsensent; KRYUKOVSKIY, S.S., prof., retsenzent
[deceased]; KRYTOV, G.M., dots., retsenzent; RAKIVNENKO,
V.N., st. prepod., retsenzent; VINOKUROV, A.I., otv. red.;
VAYNRERG, D.A., red.

[Strength of materials in examples and problems] Soprotiv-
lenie materialov v primerakh i zadachakh. Khar'kov, Izd-
vo Khar'kovskogo gos. univ., 1965. 314 p. (MIRA 18:5)

LYUBOSHITS, Moisey Il'ich; ITSKOVICH, Georgiy Mikhaylovich;
TATUR, G.K., doktor tekhn.nauk, retsenzent; BARANOVSKIY,
N.V., kand. tekhn. nauk, nauchn. red.; LEVINA, S.G., red.

[Manual on the strength of materials] Spravochnik po
soprotivleniiu materialov. Minsk, Vysshaya shkola, 1965.
343 p. (MIRA 18:5)

ITSKOVICH, G.M.; KISELEV, V.A.; CHERNAVSKIY, S.A.; BOBKOV, K.N.;
PANICH, B.B.; BAZHENOV, D.V., red.

[Preparation of a course project on machine parts; reference
manual] Kursovoe proektirovanie detalei mashin; uchebno-
spravochnoe posobie. Izd.4., perer. Moskva, Mashinostroenie
1964. 594 p. (MIRA 18:5)

Source: Staff, No. 7, 1965, 595-602

1. Batch, batching, continuous process, chemical
2. batch, batching, continuous process, chemical

[illegible]

of steel sheet. The oxygen content within narrow limits. The pouring speed
were kept within the limits of 0.4 to 0.5 m/min, while the pouring temperature is
valley control in the production of ingots is very

L 61915-65

ACCESSION NR: AP5017644

3

Chemical analysis is presented, showing the ef-
fect of the composition and surface quality. Chemical
analysis is compared to that of the ex-
isting mechanical properties for the pro-
duction of the leading part of the ingot. The
analysis of the solid rolled sheet is presented in
Table 1. Sampling experiments were carried out on the fil-
lows. The surface appearance of samples was

found to be very satisfactory in the production of automobile sections. One section
has: 4 figures, 3 tables.

ASSOCIATION: TsNIICM

1-1

SIB-17 44, 11

1-1 11

ITSKOVICH, Georgiy Mikhaylovich; VINOKUROV, Anatoliy Ivanovich;
BARANOVSKIY, Nikolay Vasil'yevich; SHAURAK, Ye.N., red.

[Collection of problems on the strength of materials]
Sbornik zadach po soprotivleniyu materialov. Leningrad,
Sudostroenie, 1965. 284 p. (MIRA 18:7)

$$T_{\text{eff}}(t) = T_{\text{eff}}(t_0) + \frac{1}{\gamma} \ln \left(\frac{F_{\text{eff}}(t)}{F_{\text{eff}}(t_0)} \right) + \frac{1}{\gamma} \ln \left(\frac{F_{\text{eff}}(t)}{F_{\text{eff}}(t_0)} \right) + \frac{1}{\gamma} \ln \left(\frac{F_{\text{eff}}(t)}{F_{\text{eff}}(t_0)} \right)$$

電話 135,785 電報 1711 電報掛號 1711
電掛 19,147 電掛 146

Ref. 4 19, 247 R. 2 106

10. *Field of study* (date of technical sciences)

... for the production of concentrated paper

... .. asting, continuous process, chemical
... .. oil-sling, sheet metal, mechanical

1. The first group of products is made of steel and is used for the construction of bridges, buildings, and other structures. This group includes products such as steel beams, plates, and pipes.

... of the Nong-fila and the Nong-fila plants, results
... of using this process in the production

1. The first part of the document is a list of names and titles, including "The Hon. Mr. Justice" and "The Hon. Mr. Justice".

~~carbon steel, 0.10-0.12% C, for the production of cold-chamber automotive shafts.~~
The continuous casting was done at the Novo-Tula and the Novolipetsk plants. Results
were conclusive in showing the possibility of using this process in the production
of steel. It is necessary to strictly control the state of oxidation of the
metal during casting. The metal must be cast within narrow limits. The pouring speed
must be controlled at 4-5 m/min, while the pouring temperature is
controlled at 1600-1620°C. Quality control in the production of ingots is very

L 61915-65

ACCESSION NR: AP5017688

3

important, and macrostructures of the finished ingots are presented, showing the effect of the annealing process on the distribution of porosity and surface quality. Chemical analysis of the finished ingots is low compared to that of the ordinary ingots, and this results in more uniform mechanical properties for the product. The results are also presented, since the leaving part of the ingot did not have the same mechanical properties as the cold rolled sheet.

has: 4 figures, 3 tables.

ASSOCIATION: T₅NTICHM

4. 27
TIEF 244

SUB CODE MM, DE

ITSKOVICH, G. M.

ITSKOVICH, G. M.

6563

ITSKOVICH, G. M. SOPROTIVLENIYE MATERIALOV.
PROGRAMMA, METOD. UKAZANIYA I KONTROL' NYE ZADANIYA.
DLYA UCHASHEHIKHSYA ZAOEH. MASHINOSTROIT. TEKHNIKUMOV. M.
SOV. NAUKA, 1954 120 S. S CHERT. 22SM. (M*VO VYSSH.
OBRAZOVANIYA. UPR. SRED. SPETS UCHEB. ZAVEDENIY) 41.000
EKZ. 2R 10 K. --NA OBL. AVT. NE UKAZAN. **
(55-2309) 620.1:539.4(071.4)

SO: KNIZHANYA LETOPIS' NO. 6, 1955

BATURIN, A.T.; ITS KOVICH, G.M., inzhener, nauchnyy redaktor; OLINER, B.M.,
inzhener, redaktor; KIROGANO V, V.G., inzhener, redaktor graficheskikh
rabot; MODEL', B.I., tekhnicheskly redaktor

[Machine parts] Detali mashin, Izd. 2-e perer. Moskva, Gos. nauchno-
tekh. izd-vo mashinostroit. lit-ry, 1954. 423 p. (MLRA 7:8)
(Machinery--Construction)

ITSKOVICH, G. M.

PAVLOV, Ya.M., kandidat tekhnicheskikh nauk, dotsent; ~~ITSKOVICH, G.M.~~,
inzhener, retsenzent; POLYAKOV, V.S., kandidat tekhnicheskikh
nauk, redaktor; FETISOV, F.I., inzhener, redaktor.

[Machine parts] Detali mashin. Moskva, Gos. nauchno-tekhn. izd-
vo mashinostroitel'noi i sudostroitel'noi lit-ry. Moskva, 1954.
480 p. (MLRA 7:7)

1. Leningradskiye otdeleniye Mashgiz. Zaveduyushchiy redaktsiei
(for Fetisov)
(Machinery)

PAVLOV, Yakov Mikhaylovich, kandidat tekhnicheskikh nauk, dotsent; POLYAKOV, V.S.,
kandidat tekhnicheskikh nauk, redaktor; ITS KOVICH, G.M., inzh-
ner, retsenzent; SIMONOVSKIY, L.Z., redaktor; POL'SKAYA, R.G., tekhnii-
cheskiy redaktor

[Machine parts] Detali mashin. Izd. 2-e, ispr. i dop. Moskva, Gos.
nauchno-tekhn. izd-vo mashinostroit. lit-ry, 1955. 559 p.
(Machinery--Design) (MLRA 9:4)

ITSKOVICH, G.M.; PANICH, B.B.; YERDAKOV, V.I.; CHERNAVSKIY, S.A., red.;
ANOSHINA, K.I., red. izd-va; PAVLOVA, V.A., tekhn. red.

[Engineering mechanics: a program, tasks for control operations, and brief instructions for fulfilling them for instruction engineering students in correspondence schools of technology and their branches] Tekhnicheskaya mekhanika; programma, zadaniya dlya kontrol'nykh rabot i kratkie ukazaniya k ikh vypolneniyu dlya uchashchikhsya stroitel'nykh spetsial'nostei zaochnykh tekhnicheskikh i otdelenii. Moskva, Gos. izd-vo "Sovetskaya nauka," 1957. 106 p. (MIRA 14:6)

(Building—Study and teaching)

ITSKOVICH, G.M.; KISELEV, V.A.; CHERNAVSKIY, S.A.; BOKOV, K.N.; PAGEL',
A.Z.; BONCH-OSMOLOVSKIY, M.A.; GRINCHAR, G.N.; CHERNAVSKIY, S.A.,
kandidat tekhnicheskikh nauk, nauchnyy redaktor; TIKHONOV, A.Ya.,
tekhnicheskiy redaktor

[Collection of problems and methods of calculating machine parts]
Sbornik zadach i primerov rascheta detalei mashin. Moskva, Gos.
nauchno-tekhn. izd-vo mashinostroit. lit-ry, 1957. 267 p. (MIRA 10:4)
(Machinery--Design)

ITSKOVICH, G.M.

BATURIN, Aleksandr Timofeyevich [deceased]; ITSKOVICH, G.M., inzhener,
nauchnyy red.; KARGANOV, V.G., inzhener, red.graficheskikh rabot;
UVAROVA, A.F., tekhn.red.

[Machine parts] Detali mashin. Izd. 3-e, perer. Moskva, Gos.
nauchno-tekhn.izd-vo mashinostroit. lit-ry, 1957. 423 p. (MIRA 10:12)
(Machinery)

ITSKOVICH, G.M.

AUTHORS: Bokov, K.N., Itskovich, G.M., Kiselev, V.A., Chernavskiy, S.A. Call No. TF 230 .K8

TITLE: Undergraduate Course in Design of Machine Elements, (Kursovoye proyektirovaniye detaley mashin) (Uchebno-spravochnoye posobiye)

PUB. DATA: Gosudarstvennoye nauchno-tekhnicheskoye izdatel'stvo mashinostroitel'noy literatury, Moscow, 1957, 2d ed. rev., 503 pp., 25,000 copies

ORIG. AGENCY: None given

EDITORS: Ed of Publishing House: Krylov, V.I., Engr.; Science Ed.: Itskovich, G.M., Engr.; Tech. Editors: Tikhanov, A.Ya., and Sokolova, T.F.; Corrector: Matisen, V.G.

PURPOSE: This book is approved by the Administration of Special Secondary Educational Institutions, Ministry of Higher Education of the USSR, as a text for technical schools.

Card 1/10

Undergraduate Course in Design of Machine Elements. Call No. TF 230.K8
(Cont.)

COVERAGE: The book is stated to contain the basic data and instructions for designing the drive mechanisms which are the standard subjects of study in courses in machine design at USSR technical schools. Typical design problems and calculations are given. The authors stress the importance of conducting student examinations in basically the same way as that in which students defending theses are examined. Chapter XIV was written with the assistance of Bonch-Osmolovskiy, M.A., Candidate of Technical Sciences, and Grinchar, G.N., Candidate of Technical Sciences. There are 34 references, all USSR.

Card 2/10

Undergraduate Course in Design of Machine Elements

Call No. TF 230 .K8
(Cont.)

TABLE OF CONTENTS

Preface to Second Edition	3
Introduction	5
Ch. I. Project Assignments in Undergraduate Courses of Machine-Element Design	7
1. Scope and subjects of assignments (Istkovich, G.M., Engr.,)	7
2. Assignment examples (Bokov, K.N., Engr.)	10
Ch. II. Preparation of Drawings and Project Reports	22
3. Fundamentals of drawing and drafting room practice	22
4. Surface quality symbols in drafting	31
5. Tolerance symbols in drafting (Bokov, K.N., Engr)	33
Card 3/10 6. Procedures for preparation of project reports	36

Undergraduate Course in Design of Machine Elements. (Cont.)		Call No. TF 230 .K8
Ch. III.	Kinematics of Drive Mechanisms and Selection of an Electric Motor (Chernavskiy, S.A., Candidate of Technical Sciences)	
	7. Determination of electric motor size	41
	8. Basic information on motor types	41
	9. Basic data on three-phase induction	44
	10. Types of three-phase induction motors	45
	11. Determination of the overall velocity ratio and its subdivision	47
Ch. IV.	General Information on Reducers (Itskovich, G.M.)	49
	12. Basic types of reducers	52
	13. Procedures for subdividing the overall velocity ratio of compound reducers into individual gear trains	52
Ch. V.	Design of Gear Drives (Itskovich, G.M.)	67
	14. General information	69
Card 4/10		69

Undergraduate Course in Design of Machine Elements. (Cont.)	Call No. TF 230 .K8	
15. Straight-tooth spur gear transmissions		70
16. Helical and herringbone spur gear transmissions		76
17. Straight-tooth bevel gear transmissions		79
18. Increment load coefficient		82
19. Gear materials and allowable stresses		86
Ch. VI. Worm Gear Transmission Design (Itskovich, G.M.)		93
20. General information and kinematics of gear transmissions		93
21. Basic characteristics and gear transmission efficiency		94
22. Gear tooth design for contact and bending strength		99
23. Materials and allowable stresses		103
Card 5/10 24. Worm gear design for strength and rigidity		105

Undergraduate Course in Design of Machine Elements. (Cont.)		Call No. TF 230 .K8
Ch. VII.	Shaft Design (Itskovich, G.M.)	109
25.	Shaft loads	109
26.	Shaft design procedures	113
27.	Key and spline connections	121
Ch. VIII.	Design of Shaft Rolling Bearings	127
28.	Procedure of bearing-assembly design	127
29.	Selection of bearing type	128
30.	Basic methods and requirements for design of assemblies	133
31.	Shaft and block-bearing fits	143
32.	Mounting of outer and inner bearing rolls	150
33.	Installation requirements for mounting bearing assemblies	159
34.	Selection of bearings on the basis of performance rating and static load capacity	160

Card 6/10

Call No. TF 230 .K8

Undergraduate Course in Design of Machine Elements. (Cont.)

	35. Bearing-assembly packing	168
	36. Rolling-bearing lubrication	175
Ch. IX.	Design of Sliding-Contact Bearing for Reducers. (Chernavskiy, S.A.)	183
	37. General information	183
	38. Design of sliding-contact bearing	183
Ch. X.	Design of Reducer Elements. Gear and Worm Lubrication (Kiselev, Engr.)	195
	39. Gear, worm-gear, and worm design	195
	40. Design of reducer blocks	210
	41. Reducer lubrication	224
	42. Operating-temperature considerations in the design of reducers	231
Card 7/10	43. Classification of fits for basic reducer elements	232

Call No. TF 230 .K8

Undergraduate Course in Design of Machine Elements. (Cont.)

Ch. XI.	Belt-Drive Design (Chernavskiy, S.A.)	234
	44. Flat-belt drive	234
	45. Tension pulley drives	245
	46. V-belt drive	247
Ch. XII.	Design of Chain Drives (Chernavskiy, S.A.)	255
	47. General information	255
	48. Basic symbols and design relations	258
	49. Methods of chain design	262
Ch. XIII.	Coupling and Clutch Design (Chernavskiy, S.A.)	271
	50. Brief review of couplings and clutches	271
	51. Coupling and clutch design data	271
	52. Types and design of couplings and clutches	272

Card 8/10

Undergraduate Course in Design of Machine Elements: (Cont.)		Call No. TF 230. K8
Examples of How to Design Drive Mechanisms		
Ch. XIV.	Examples of simple reducer design	313
53.	Design of a simple spur-gear reducer (Itskovich, G.M., and Bonch-Osmolovskiy, M.A., Candidate of Technical Sciences)	313
54.	Design of a bevel-gear reducer (Itskovich, G.M., and Grinchar, G.N., Candidate of Technical Sciences)	330
55.	Design of a worm-gear reducer (Itskovich, G.M. and Grinchar, G.N.)	348
Ch. XV.	Examples of design of Two-stage Reducers with Gear Train	363
56.	Design of a two-stage spur-gear reducer drive (Kiselev, V.A.)	363
57.	Design of a bevel-spur gear reducer drive (Kiselev, V.A.)	399
58.	Design of a worm-gear reducer drive (Kiselev, V.A.)	426
59.	Design of a screw conveyor with belt and bevel-gear drives (Bokov, K.N.)	448

PAVLOV, Yakov Mikhaylovich, dotsent, kand.tekhn.nauk; ITSEKOVICH, G.M.,
inzh., retsensent; POLYAKOV, V.S., dotsent, kand.tekhn.nauk,
red.; SIMONOVSKIY, N.Z., red.isd.; POL'SKAYA, R.G., tekhn.red.

[Machine parts] Detali mashin. Moskva, Gos.nauchno-tekhn.
isd-vo mashinostroit.lit-ry, 1958. 511 p. (MIRA 12:3)
(Machinery--Design)

ITSKOVICH, G.M.; KISILEV, V.A.; CHERNAVSKIY, S.A., kand.tekhn.nauk;
BOKOV, K.M.; FAGEL', A.Z.; BONGH-OSMOLOVSKIY, M.A.; GRINCHAR,
G.M.; EL'KIND, V.D., tekhn.red.

[Collected problems and exercises of design for the course on
machine parts] Sbornik zadach i primerov rascheta po kursu
detalei mashin. Izd.2-e, perer. Moskva, Gos.nauchno-tekhn.
izd-vo mashinostroit.lit-ry, 1959. 330 p. (MIRA 13:10)
(Mechanical engineering--Problems, exercises, etc.)

ITSKOVICH, G.M.

PHASE I BOOK EXPLOITATION SOV/3453

Chernavskiy, Sergey Aleksandrovich, Georgiy Mikhaylovich Itskovich, Vyacheslav Aleksandrovich Kiselev, Kirill Nikolayevich Bokov, Mikhail Aleksandrovich Bonch-Osmolovskiy, and Boris Pavlovich Kozintsov

Proyektirovaniye mekhanicheskikh peredach; uchebno-spravochnoye posobiye po kursovomu proyektirovaniyu detaley mashin (Designing of Mechanical Drives; Text and Handbook On Machine Parts Designing) Moscow, Mashgiz, 1959. 740 p. 80,000 copies printed.

Scientific Ed.: S.A. Chernavskiy; Ed. of Publishing House: N.Yu. Blagosklonova, Engineer; Tech. Ed.: A.Ya. Tikhonov; Managing Ed. for Information Literature: I.M. Monastyrskiy, Engineer.

PURPOSE: This manual is intended for students in higher engineering schools.

COVERAGE: This book describes the basic principles of the kinematic design of drives with a consideration of economy
Card 1/8